

Synthesis Introduces a new, superior approach to tubes amplifier design. ROMA series has been created to breathe life into the melodious weft of the fabric of music, in all its nuances, making the listening experience an extraordinarily moving event. Created by those obsessed with great sound and for those who love great music.

There has never been an introductory integrated amplifier with the fit, finish and sound of the ROMA 753AC. At first glance, this stunning amp simply takes your breath away. This high performance amplifiers brings out the best of other components in the system. Created by those obsessed with great sound and for those who love great music. The result is 50 watts of pure pentode output per channel built around a pair of 12AU7 on input/driver tubes and a pair of EL34/6CA7 power tubes in push-pull configuration for a detailed, delicate and dynamic sound.



# ROMA 753AC

# Technical specifications:

Power stage (1 ch.): 2 X 6CA7/EL34

Driver (1 ch.): ECC82/12AU7

Input stage (1 ch.): ECC82/12AU7

Frequency response: 20Hz to 20KHz +- 0.5dB

Input impedance: 50Kohm Input sensitivity: 300mV / 50W

Output impedance: 6 ohm
Power stage config.: Pentode

Power output: 50W RMS AB Class Signal/Noise ratio: >90dB, A weighted

Inputs: 5 Line

Outputs: Pre Output (Volume controlled)

Power consumption: 250W

Dimensions: (w,d,h) 410x330x260mm

Weight: 20.0 Kg

Remote control:

Transmit: RC5 Infrared code Function: Mute, Volume, Inputs Dim.s: (w,d,h) 45x160x25 mm

Weight: 150 gr. (Battery included)

# **FEATURES**

#### -DC Powered tube heater

All tubes, except EL34, have DC stabilised heater circuits to reduce hum noise to a near in-audible minimum.

## Output transformer

The Output transformer uses a Hi-Grade Iron-Silicon for superb frequency reproduction & width. With this newly designed custom output transformer we are able to achieving a highly delicate & precise sound reproduction faithful to the original recording.

#### - Mechanical chassis construction

The power supply & output transformers are held by an extremely rigid structure that keeps the unit free from unwanted vibrations which further helps reduce unwanted noise to the tubes.

### - Remote control

It has a soft button design, perfectly matching the aesthetics for the "ROMA" series. It controls volume, mute and sources selection.

#### - Feet

Four aluminium feet with an insert of strong rubber. These rubber feet has been choise to minimise vibrations of the amplifier in isolation from its surroundings.

# - Binding posts

Gold plated professional binding posts for a continued oxidisation free connection further improve sound refinement.

#### - Sockets

Gold plated ceramic sockets for a continued oxidisation free connection further improve sound refinement.

## - Components

Components for the Roma 753AC have been selected with great care throughout. Only the best available components are considered & all must undergo an exhaustive analysis of their sonic influence prior to final selection.

## - Selected tubes

All tubes used are selected after 2 stage warm up. A fully computer monitored machine controls the process & at the end of this, selects the perfect tubes which are then matched for a perfect balance.